

FORTINET®

High Performance Network Security

PRODUCT MATRIX



JANUARY 2015



FortiGate® Network Security Platform - *Top Selling Models Matrix

| | FG/FWF-30D | FG/FWF-60D | FG-80D | FG-70D, FG/FWF-90D | FG/FWF-92D | FG-100D | FG-200D | FG-300D | FG-500D | FG-800C |
|--|--|--|--|--|---------------------------|--|---|--------------------------------------|--------------------------------------|--|
| Firewall Throughput (1518/512/64 byte UDP) | 0.8 / 0.8 / 0.8 Gbps | 1.5 / 1.5 / 1.5 Gbps | 1.3 / 0.95 / 0.17 Gbps | 3.5 / 3.5 / 3.5 Gbps | 2.0 / 1.0 / 0.2 Gbps | 2.5 / 1 / 0.2 Gbps | 3 / 3 / 3 Gbps | 8 / 8 / 8 Gbps | 16 / 16 / 16 Gbps | 20 / 20 / 20 Gbps |
| Firewall Latency | 8 µs | 4 µs | 90 µs | 4 µs | 46 µs | 37 µs | 2 µs | 3 µs | 3 µs | 6 µs |
| Concurrent Sessions | 200,000 | 500,000 | 1.5 Million | 2 Million | 1.5 Million | 3 Million | 3.2 Million | 6 Million | 6 Million | 7 Million |
| New Sessions/Sec | 3,500 | 4,000 | 22,000 | 4,000 | 22,000 | 22,000 | 77,000 | 200,000 | 280,000 | 190,000 |
| Firewall Policies | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 10,000 | 10,000 | 10,000 | 10,000 | 10,000 |
| IPSec VPN Throughput | 350 Mbps | 1 Gbps | 200 Mbps | 1 Gbps | 130 Mbps | 450 Mbps | 1.3 Gbps | 7 Gbps | 14 Gbps | 8 Gbps |
| Max G/W to G/W IPSEC Tunnels | 20 | 200 | 200 | 200 | 200 | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 |
| Max Client to G/W IPSEC Tunnels | 250 | 500 | 1,000 | 1,000 | 1,000 | 5,000 | 5,000 | 10,000 | 10,000 | 50,000 |
| SSL VPN Throughput | 25 Mbps | 30 Mbps | 130 Mbps | 35 Mbps | 170 Mbps | 300 Mbps | 400 Mbps | 350 Mbps | 400 Mbps | 1.3 Gbps |
| Recommended SSL VPN Users | 80 | 100 | 200 | 200 | 200 | 300 | 300 | 500 | 500 | 10,000 |
| IPS Throughput | 150 Mbps | 200 Mbps | 800 Mbps | 275 Mbps | 950 Mbps | 950 Mbps | 1.7 Gbps | 2.8 Gbps | 4.7 Gbps | 6 Gbps |
| Antivirus Throughput (Proxy-Based/ Flow-Based) | 30 / 40 Mbps | 35 / 50 Mbps | 250 / 550 Mbps | 35 / 65 Mbps | 300 / 700 Mbps | 300 / 700 Mbps | 600 / 1,100 Mbps | 1.4 / 2.5 Gbps | 1.7 / 3.4 Gbps | 1.7 / 3.1 Gbps |
| Max FortiAPs (Total / Tunnel) | 2 / 2 | 10 / 5 | 32 / 16 | 32 / 16 | 32 / 16 | 64 / 32 | 128 / 64 | 512 / 256 | 512 / 256 | 1024 / 512 |
| Max FortiTokens | 20 | 100 | 100 | 100 | 100 | 1,000 | 1,000 | 1,000 | 1,000 | 1,000 |
| Max Registered FortiClient | 200 | 200 | 200 | 200 | 200 | 600 | 600 | 600 | 2,000 | 2,000 |
| Virtual Domains (Default/Max) | - | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 |
| Interfaces | 5x GE RJ45 | 10x GE RJ45 | 4x GE RJ45 | 16x GE RJ45 | 16x GE RJ45 | 20x GE RJ45, 2x Shared Port Pairs (100D only) | 18x GE RJ45, 2x GE SFP | 6x GE RJ45, 4x GE SFP | 10x GE RJ45, 8x GE SFP | 2x 10GE SFP+, 14x GE RJ45, 8x Shared Port Pairs, 2x Bypass Pairs |
| Local Storage | - | - | 16 GB | FG/FWF-90D: 32 GB | 16 GB | 32 GB | 64 GB | 120 GB | 120 GB | 60 GB |
| Power Supplies | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply, opt. Ext RPS | Single AC Power Supply, opt. Ext RPS | Single AC Power Supply, opt. Ext RPS | Single AC Power Supply, opt. Dual PS or Ext RPS |
| Form Factor | Desktop | Desktop | Desktop | Desktop | Desktop | Rack Mount, 1 RU | Rack Mount, 1 RU | Rack Mount, 1 RU | Rack Mount, 1 RU | Rack Mount, 1 RU |
| Variants | WiFi, POE | WiFi, POE, LENC | - | WiFi, POE, LENC, High port density + POE | WiFi | LENC, High port density, High port density + POE | LENC, POE, High port density, High port density + POE | - | - | DC |
| | FG-1000D | FG-1200D | FG-1500D | FG-3240C | FG-3200D | FG-3700D | FG-3950B | FG-5001C | FG-5101C | FG-5001D |
| Firewall Throughput (1518/512/64 byte UDP) | 52 / 52 / 33 Gbps | 72 / 72 / 50 Gbps | 80 / 80 / 55 Gbps | 40 / 40 / 40 Gbps | 80 / 80 / 50 Gbps | 160 / 160 / 110 Gbps | 20-120 / 20-120 / 20-120 Gbps | 40 / 40 / 40 Gbps | 40 / 40 / 10 Gbps | 80 / 80 / 45 Gbps |
| Firewall Latency | 3 µs | 3 µs | 3 µs | 4 µs | 3 µs | 2 µs | 4 µs | 4 µs | 7 µs | 3 µs |
| Concurrent Sessions | 11 Million | 11 Million | 12 Million | 10 Mil | 50 Million | 50 Million | 20 Million | 29.5 Million | 10 Million | 23 Million |
| New Sessions/Sec | 240,000 | 240,000 | 250,000 | 200,000 | 280,000 | 300,000 | 250K - 300K** | 210,000 | 235,000 | 565,000 |
| Firewall Policies | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 |
| IPSec VPN Throughput | 30 Gbps | 40 Gbps | 50 Gbps | 17 Gbps | 50 Gbps | 100 Gbps | 8 - 50.5 Gbps | 17 Gbps | 22 Gbps | 25 Gbps |
| Max G/W to G/W IPSEC Tunnels | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 | 40,000 | 40,000 | 40,000 | 40,000 | 40,000 |
| Max Client to G/W IPSEC Tunnels | 50,000 | 50,000 | 50,000 | 64,000 | 64,000 | 64,000 | 64,000 | 64,000 | 64,000 | 64,000 |
| SSL VPN Throughput | 3.6 Gbps | 3.6 Gbps | 4 Gbps | 3.4 Gbps | 8 Gbps | 10 Gbps | 1.2 Gbps | 3.6 Gbps | 1.3 Gbps | 6.5 Gbps |
| Recommended SSL VPN Users | 10,000 | 10,000 | 10,000 | 30,000 | 30,000 | 30,000 | 25,000 | 20,000 | 25,000 | 25,000 |
| IPS Throughput | 8 Gbps | 11 Gbps | 11 Gbps | 8 Gbps | 14 Gbps | 23 Gbps | 5- 20 Gbps | 12 Gbps | 9.4 Gbps | 18 Gbps |
| Antivirus Throughput (Proxy-Based/ Flow-Based) | 3.5 / 5.5 Gbps | 3.5 / 10 Gbps | 4.3 / 13 Gbps | 2.6 / 9 Gbps | 5.7 / 16 Gbps | 7.5 / 18 Gbps | 4 / 5 - 15 Gbps | 3 / 4 Gbps | 2 / 5 Gbps | 5.6 / 13 Gbps |
| Max FortiAPs (Total, Tunnel) | 4,096 / 1,024 | 4,096 / 1,024 | 4,096 / 1,024 | 4096 / 1024 | 4096 / 1024 | 4,096 / 1,024 | 4,096 / 1,024 | 4,096 / 1,024 | 4,096 / 1,024 | 4,096 / 1,024 |
| Max FortiTokens | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 |
| Max Registered Endpoints | 8,000 | 8,000 | 8,000 | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 |
| Virtual Domains (Default/Max) | 10 / 250 | 10 / 250 | 10 / 250 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 |
| Interfaces | 2x 10 GE SFP+, 16x GE SFP, 18x GE RJ45 | 4x 10 GE SFP+, 16x GE SFP, 18x GE RJ45 | 8 x 10GE SFP+, 16x GE SFP, 18x GE RJ45 | 12x 10GE SFP+, 2x GE RJ45, 16x GE SFP | 48x 10GE SFP+, 2x GE RJ45 | 4 x 40GE QSFP+, 20 x 10GE SFP+/GE SFP, 8 x SFP+, 2 x GE RJ45 | 2x 10GE SFP+, 4x GE SFP , 2x GE RJ45 | 2x 10GE SFP+, 2x GE RJ45 | 4x 10GE SFP+, 2x GE RJ45 | 2x 40GE QSFP+, 2x 10GE SFP+, 2x GE RJ45 |
| Local Storage | 120 GB | 120 GB | 240 GB | 64 GB | 960 GB | 960 GB | 256 GB | 128 GB | 64 GB | 200 GB |
| Power Supplies | Dual PS | Dual PS | Dual PS | Dual PS | Dual PS | Dual PS | Dual PS | Chassis Based | Chassis Based | Chassis Based |
| Form Factor | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 3 RU | Rack Mount, 3 RU | ATCA Blade | ATCA Blade | ATCA Blade |
| Variants | - | - | - | DC | - | DC | DC, LENC | - | - | - |

* Featured Top selling models, for complete FortiGate offerings please visit www.fortinet.com. FortiGate virtual appliances are also available. Specifications based on FortiOS V5.2+

** With FMC-XHD

FortiManager™ Centralized Management Platform

| | FMG-200D | FMG-300D | FMG-1000D | FMG-3900E | FMG-4000E | FMG-VM-BASE | FMG-VM-10-UG | FMG-VM-100-UG | FMG-VM-1000-UG | FMG-VM-5000-UG | FMG-VM-U-UG |
|---------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------------|--------------|---------------------|---------------------|---------------------|---------------------|
| Max Licensed Devices/ADoms | 30 | 300 | 1,000 | 10,000 | 4,000 | 10 | +10 | +100 | +1,000 | +5,000 | Unlimited |
| Max Web Portals/Users | - | - | 1,000 | 10,000 | 4,000 | 10 | +10 | +100 | +1,000 | +5,000 | Unlimited |
| GB Logs/Day | 2 | 2 | 2 | 10 | 10 | 1 | 2 | 5 | 10 | 25 | 50 |
| Locally Hosted Security Content | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM | AV, IPS, VM | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45 | 6x GE RJ45, 2x SFP | 2x GE, 2x GE SFP+ | 4x GE RJ45, 2x SFP | 1 / 4 (vNIC Min / Max) | | | | | |
| Storage Capacity | 1x 1 TB | 2x 2TB | 4x 2 TB | 15x 960 GB | 8x 2 TB | 80 GB / 16 TB (Min / Max) | | | | | |

FortiAnalyzer™ Centralized Logging & Reporting Solution

| | FAZ-200D | FAZ-300D | FAZ-1000D | FAZ-2000B | FAZ-3000E | FAZ-3500E | FAZ-3900E | FAZ-VM-BASE | FAZ-VM-GB1 | FAZ-VM-GB5 | FAZ-VM-GB25 | FAZ-VM-GB100 |
|-----------------------------------|------------|----------------|------------------------------------|--------------------------------|------------------------------------|------------------------------------|------------------------------------|-------------|------------|------------|-------------|--------------|
| GB Logs/Day | 5 | 15 | 25 | 75 | 250 | Unrestricted* | Unrestricted* | 1 | +1 | +5 | +25 | +100 |
| Sessions/Day | 18 Mil | 55 Mil | 85 Mil | 260 Mil | 850 Mil | Unrestricted* | Unrestricted* | 3.5 Mil | 3.5 Mil | 18 Mil | 85 Mil | 360 Mil |
| Peak Log Rate (standalone Mode) | 350 | 625 | 1,000 | 5,000 | 50,000 | 60,000 | 75,000 | - | - | - | - | - |
| Max. Licensed Devices/VDOMs/ADOMs | 150 | 175 | 2,000 | 2,000 | 4,000 | 4,000 | 4,000 | 10,000 | 10,000 | 10,000 | 10,000 | 10,000 |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45 | 6x GE RJ45, 2x SFP | 6x GE RJ45 | 4x GE RJ45, 2x GE SFP | 2x GE RJ45, 2x GE SFP | 2x GE RJ45, 2x GE SFP+ | - | - | - | - | - |
| Storage Capacity | 1x 1 TB | 2x 2 TB | 4x 2 TB | 2x 2 TB (12 TB Max) | 8x 2 TB (16 TB Max) | 12x 2 TB (48 TB Max) | 15x 960 GB | 200 GB** | 200 GB** | 1 TB** | 8 TB** | 16 TB** |
| RAID Support | No | Yes (Mirrored) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | Yes, (RAID 0, 1, 5, 6, 10, 50) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | - | - | - | - | - |

* Only restricted to the hardware platform performance (e.g. there are no software licensing limitations)

** Device quota is not stackable, this represents the maximum quota available with purchased license.

FortiAP™ (Indoor) Wireless Access Point

| | FAP-24D | FAP-221B/223B | FAP-221C/223C | FAP-320B | FAP-320C | FAP-321C |
|---|---|---|---|--|--|--|
| Suggested Use Case | Low density indoor | Medium density indoor | Medium density indoor | Indoor high performance AP | high density 802.11ac, streaming app resilience | Medium density 802.11ac without resilience |
| IEEE Standard | 802.11 a/b/g/n | 802.11 a/b/g/n | 802.11 a/b/g/n/ac | 802.11 a/b/g/n | 802.11 a/b/g/n/ac | 802.11 a/b/g/n/ac |
| Number of Radio / Antennas | 1 / 2 Internal | 221B: 2 / 4 Int. 223B: 2 / 4 Ext. | 221C: 2 / 4 Int. 223C: 2 / 4 Ext. | 2 / 6 internal | 2 / 6 internal | 2 / 6 internal |
| MIMO (Total Association Rate) | 2x2 MIMO dual spatial stream (300 Mbps Total) | 2x2 MIMO dual spatial stream (600 Mbps Total) | 2x2 MIMO dual spatial stream (1,167 Mbps Total) | 3x3 MIMO with 3 spatial streams (900 Mbps Total) | 3x3 MIMO with 3 spatial streams (1,750 Mbps Total) | 3x3 MIMO with 3 spatial streams (1,750 Mbps Total) |
| Total (Client access + Monitoring) Simultaneous SSIDs | 16 | 16 | 16 | 16 | 16 | 16 |
| Max Transmission Power | 18dBm (63mW) | 17dBm (50mW) | 20 dBm (100mW) | 24 dBm (250mW) * | 21 dBm (126mW) * | 20 dBm (100mW) |
| Ethernet Interface | 1x GE WAN, 4x FE LAN | 1x GE RJ45 | 1x GE RJ45 | 2x GE RJ45 | 2x GE RJ45 | 1x GE RJ45 |
| Power over Ethernet (PoE) | 802.3af | 802.3af | 802.3af | 802.3af | 802.3af | 802.3af |

* Frequency selection and power may be restricted to abide by regional regulatory compliance laws.

For Complete selection of FortiAPs, including remote and outdoor devices, please refer to Fortinet Wireless Solution Matrix

FortiSwitch™ Secured Access Switch

| | FSW-28C | FSW-108D-POE | FSW-224D-POE | FSW-324B-POE | FSW-348B | FSW-448B |
|-------------------------------------|----------------------------------|--|---|--|----------------------------------|--------------------------|
| Total Interfaces | 8 x GE RJ45 LAN, 2 x GE RJ45 WAN | 8x GE POE RJ45 ports, 2x Shared Port Pairs | 20x GE RJ45 ports (incl. 12 PoE), 4x GE Shared Port Pairs | 16x GE PoE, 4x GE PoE+, 4x Shared Port Pairs | 48 GE RJ45, 2x Shared Port Pairs | 48 GE RJ45, 2x 10GE SFP+ |
| Switch Capability | 16 Gbps | 20 Gbps | 48 Gbps | 48 Gbps | 96 Gbps | 136 Gbps |
| FortiGate Switch Controller Support | Yes (Remote) | Yes | Yes | Yes | Yes | Yes |

For Complete selection of FortiSwitches, please refer to <http://www.fortinet.com/products/fortiswitch>

FortiAuthenticator™ User Identity Management Server

| | FAC-200D | FAC-400C | FAC-1000D | FAC-3000D | FAC-VM Base | FAC-VM-100-UG | FAC-VM-1000-UG | FAC-VM-10000-UG | FAC-VM-100000-UG |
|------------------------------------|----------------|--------------------|-------------------------|-------------------------|----------------|-------------------|------------------------|----------------------------|-------------------------------|
| Max Local/Remote Users/ User Group | 500 / 500 / 25 | 2,000 / 2,000 / 50 | 10,000 / 10,000 / 2,000 | 40,000 / 40,000 / 4,000 | 100 / 100 / 10 | +100 / +100 / +10 | +1,000 / +1,000 / +100 | +10,000 / +10,000 / +1,000 | +100,000 / +100,000 / +10,000 |
| Max FortiToken | 500 | 2,000 | 10,000 | 40,000 | 200 | +200 | +2,000 | +20,000 | +200,000 |
| Max NAS Devices | 50 | 200 | 1,000 | 4,000 | 10 | +10 | +100 | +1,000 | +10,000 |

FortiSandbox™ Advanced Threat Prevention System

| | FSA-1000D | FSA-3000D | FSA-VM |
|----------------------------|-----------|-----------|--------------------|
| VM Sandboxing (Files/Hour) | 160 | 560 | Hardware dependent |
| AV Scanning (Files/Hour) | 6,000 | 15,000 | Hardware dependent |
| Number of VMs | 8 | 28 | Up to 52 |

FortiDDOS™ Hardware Accelerated DDoS Mitigator

| | FDD-200B | FDD-400B | FDD-800B | FDD-1000B | FDD-2000B |
|--------------------------|-----------|-----------|-----------|-----------|-----------|
| Throughput (Full Duplex) | 2 Gbps | 4 Gbps | 8 Gbps | 12 Gbps | 24 Gbps |
| Simultaneous Connections | 1 Mil | 1 Mil | 2 Mil | 3 Mil | 4 Mil |
| Session Setup/Teardown | 100 K/Sec | 100 K/Sec | 200 K/Sec | 300 K/Sec | 600 K/Sec |

FortiMail™ Messaging Security Server

| | FML-200D | FML-400C | FML-1000D | FML-3000D | FML-VM00 | FML-VM01 | FML-VM02 | FML-VM04 | FML-VM08 |
|-----------------------------|----------|----------|-----------|------------------------|----------|--------------|--------------|--------------|--------------|
| Email Routing* (Msg/Hr) | 76,000 | 150,000 | 680,000 | 1.5 Mil | 3,600 | 34,000 | 67,000 | 306,000 | 675,000 |
| Performance AS+AV* (Msg/Hr) | 58,000 | 120,000 | 500,000 | 1.3 Mil | 2,700 | 26,000 | 52,000 | 225,000 | 585,000 |
| Email Domains | 20 | 100 | 800 | 2,000 | 2 | 20 | 100 | 800 | 2,000 |
| Server Mode Mailboxes | 150 | 400 | 1,500 | 3,000 | 50 | 150 | 400 | 1,500 | 3,000 |
| Storage Capacity | 1x 1 TB | 2x 1 TB | 2x 2 TB | 2x 2 TB (12 TB Max) | 1x 146GB | 50 GB - 1 TB | 50 GB - 2 TB | 50 GB - 4 TB | 50 GB - 8 TB |

* Measured based on 100KB message size, no queuing.

FortiWeb™ Web Application Firewall

| | FWB-400C | FWB-1000D | FWB-3000D/Fsx | FWB-4000D | FWB-VM01/-VM02/- VM04/-VM08 |
|-------------------|------------|---|---|---|---------------------------------------|
| Throughput (HTTP) | 100 Mbps | 750 Mbps | 1.5 Gbps | 4 Gbps | 25 Mbps /100 Mbps/ 500 Mbps 1 Gbps |
| Total Interfaces | 4x GE RJ45 | 2x GE RJ45, 4x GE RJ45 Bypass, 2x GE SFP | 6x GE RJ45, 2x GE Bypass /Fsx: 6x GE RJ45 , 2x 10GE SFP+ Bypass | 6x GE RJ45, 2x GE RJ45 Bypass, 2x GE SX Bypass, 2x 10GE SFP+ Bypass | - |

FortiADC™ Application Delivery Controller

| | FAD-100E | FAD-200D | FAD-200E | FAD-300E | FAD-400E | FAD-600E | FAD-700D | FAD- 1000E | FAD- 1500D | FAD- 2000D | FAD- 4000D |
|-------------------|------------|------------|------------|------------|------------|------------------------|---|------------------------|------------------------|-------------------------|-------------------------|
| Throughput (HTTP) | 1 Gbps | 2.7 Gbps | 2.7 Gbps | 4.8 Gbps | 8 Gbps | 12 Gbps | 15 Gbps | 15 Gbps | 20 Gbps | 30 Gbps | 50 Gbps |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45 | 4x GE RJ45 | 6x GE RJ45 | 8x GE RJ45 | 2x 10GE, 8x GE RJ45 | 4x 10 GE SFP+, 4x GE SFP, 4x GE RJ45 | 2x 10GE, 8x GE RJ45 | 4x 10GE, 8x GE RJ45 | 4x 10GE, 16x GE RJ45 | 8x 10GE, 16x GE RJ45 |

Virtual appliances are also available, please refer to www.fortinet.com for more information

Virtual Appliance Support Matrix

| | VMWare vSphere v4.0/4.1 | VMWare vSphere v5.0/5.1/5.5 | Citrix Xen Server v5.6 SP2 | Citrix Xen Server v6.0 | Xen | KVM | Amazon AWS | Microsoft Hyper-V 2008 R2 | Microsoft Hyper-V 2012 |
|-----------------------|-------------------------------|-----------------------------------|----------------------------------|------------------------------|-----|-----|---------------|---------------------------------|------------------------------|
| FortiGate-VM | • | • | • | • | • | • | • | • | • |
| FortiManager-VM | • | • | | | | | • | • | • |
| FortiAnalyzer-VM | • | • | | | | | • | • | • |
| FortiWeb-VM | • | • | | • | • | | • | | • |
| FortiMail-VM | • | • | | | | | | • | • |
| FortiAuthenticator-VM | • | • | | | | | | • | • |
| FortiADC-VM | | • | | | | | | | |
| FortiCache-VM | • | • | | | | | | | |
| FortiVoice-VM | | • | | | | | | | |
| FortiRecorder-VM | | • | | | | | | | • |
| FortiSandbox-VM | | • | | | | | | | |

Also Available

AscenLink Link Load Balancer
FortiBridge Failopen Appliance
FortiCache Secure Web Cache
FortiCamera Network Video Security

FortiClient Host Security Client
FortiDB Database Security System
FortiDNS Secure DNS Cache
FortiExtender 3G/4G WAN Extender

FortiTap Passive Network Tap
FortiToken 2 Factor Authentication Token
FortiVoice Secure VoIP Solution

This document is provided as a convenient comparison of Fortinet products and services. The datasheet for any product or service can be found on www.fortinet.com should be consulted for the most updated specifications.

Copyright© 2014 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.

PROMTX-2015-R34-JAN